

LOW-LIGHT

HI-SPEED

SMART

RELIABLE

# IQeye700/750 series

## MEGAPIXEL NETWORK CAMERAS



## IQeye700 and IQeye750 Day/Night

Choose the IQeye700 for normal indoor/outdoor scenes and the IR Sensitive IQeye750 Day/Night for very low-light applications.

IQeye700/750 Series megapixel network cameras deliver best-in-class image quality, dynamic range and network stability you can rely on in the most challenging environments. These full featured cameras provide incredible hi-speed IQeye Resolution™ with exceptional low-light performance in a rugged, industrial compact package.

The IQeye700/750 delivers low-bandwidth video for remote viewing while simultaneously recording crisp, clear megapixel images. IQinVision continues to lead the industry in image quality, reliability and advanced camera features like PoE, on-camera storage and the Public View Port™ which makes focusing simple and integrates easily with legacy CCTV systems.


*IQeye cameras are the smart solution ...  
so you never miss a thing.*

[www.iqeye.com](http://www.iqeye.com)

**IQinvision** 

*When you can't afford to miss a thing.*

# IQeye700 and IQeye750 Day/Night Cameras



**High Resolution**



**IQeye Resolution**

## IQrecorder™

Available with every IQeye, IQrecorder enables you to record and playback crisp, clear IQeye Resolution™ images using affordable network storage *with no client software.*

## IQauthenticate™

Every IQeye is also available with on-camera, digital authentication that protects images right in the camera. IQauthenticate addresses the image manipulation problem, *at the source*, ensuring your evidence has not been compromised.



**IQeye 700/750 back panel**

- **1.3 Mpix resolution @ up to 30 ips**
- **2.0 Mpix resolution @ up to 20 ips**
- **3.1 Mpix resolution @ up to 12 ips**
- **5.0 Mpix resolution @ up to 10 ips**
- **< 0.09 Lux IR Sensitive (750 Series)**
- **MultiStream low BW + hi resolution**
- **IEEE 802.3af - Power-Over-Ethernet**
- **Public View Port™ analog output**
- **CF slot for on-camera recording**
- **LIGHTGRABBER II™ low-light feature**
- **Digital image cropping**
- **Include/Exclude exposure window**
- **Alarm IO**
- **Wide operating temperature range**
- **< 3W power AC/DC**
- **Privacy zones**
- **Auto, manual and scheduled day/night settings**

MODEL NUMBER	DESCRIPTION
IQ701	Hi-Speed, Low-Light, 1.3 Mpix DPTZ IP Camera Module (1280 x 1024)
IQ702	Hi-Speed, Low-Light, 2.0 Mpix DPTZ IP Camera Module (1600 x 1200)
IQ703	Hi-Speed, Low-Light, 3.1 Mpix DPTZ IP Camera Module (2048 x 1536)
IQ705	Hi-Speed, Low-Light, 5.0 Mpix DPTZ IP Camera Module (2592 x 1944)
IQ751	Day-Night, Hi-Speed 1.3 Mpix DPTZ IP Camera Module (1280 x 1024)
IQ752	Day-Night, Hi-Speed 2.0 Mpix DPTZ IP Camera Module (1600 x 1200)
IQ753	Day-Night, Hi-Speed 3.1 Mpix DPTZ IP Camera Module (2048 x 1536)
IQ755	Day-Night, Hi-Speed 5.0 Mpix DPTZ IP Camera Module (2592 x 1944)

CONTACT IQINVISION FOR A COMPLETE LIST OF KITS AND ACCESSORIES.

Camera dimensions (without lens) approx.  
2.52"(6.4cm)H x 2.52"(6.4cm)W x 3.94"(10.0cm)D

Camera weight (without lens) 13oz (368.5g)

For shipping weight information, please contact IQinVision.

©2006 IQinVision, Inc., IQinVision, IQeye logo are registered trademarks, and IQeye, IQpoet, IQauthenticate, IQrecorder, Resolution-On-Demand, IQeye Resolution and LIGHTGRABBER are trademarks of IQinVision. All other brands, trademarks and/or registered trademarks are property of their respective holders. 0806

*When you can't afford to miss a thing.*

**IQinvision**   
www.iqeye.com

3005 S. El Camino Real  
San Clemente, CA 92672 USA  
phone +1.949.369.8100  
fax +1.949.369.8105